



Vivopay 4000



ViVOpay 4000 integrates physically into existing and new systems by a variety of mounting options.



The ViVOpay 4000 contactless payment device adapts easily to a wide variety of existing Point of Sale (POS) terminals and Electronic Cash Register (ECR) systems providing for physical and functional integration with the merchant system and check-out lane. The small footprint (5" x 4.2" x 0.7") and flexible design of the ViVOpay 4000 was crafted to give merchants a variety of mounting options and provide for complete visual integration. With ViVOpay 4000, merchants with digital signature pads and customer or clerk-facing POS or ECRs systems will be able to start accepting contactless cards and key fobs; generating 20% larger ticket value and a 20% shift from cash and checks*.

ViVOpay 4000 is certified for MasterCard® PayPass™, Visa® contactless, ExpressPay from American ExpressSM and Discover contactless payment programs in addition to private-label contactless gift and loyalty cards.



Vivopay 4000



Benefits

- **Easy Integration:** Adapts to POS and ECR systems providing for functional and physical integration.
- **Revenue Increase:** Contactless payments generate ticket uplift and increased card usage.
- **Speed and Convenience:** Rapid check-out time during peak hours.
- **Low Cost:** Upgrading existing POS systems costs only a fraction of replacement for new contactless-enabled POS.
- **Custom Branding:** Co-brand contactless reader with your own message.

For more information, contact your ProsPay Merchant Services Sales Rep. Or visit www.tryprospay.com

FEATURES

- **Contactless:** Accepts transactions from consumers using ISO/IEC 14443 Type A and B, NFC, and Mifare cards and key fobs.
- **Compatibility:** Interfaces to a variety of POS and ECR host systems from leading vendors such as VeriFone, Ingenico, Hypercom, Lipman, NCR, Radiant, IBM, Sharp, Micros, Partech, @POS, xpient, Compris, Aloha.
- **Speed:** Enables quick transactions improving store productivity and operational efficiencies.
- **Implementations:** Retail locations, ticket booths, multi-lane merchants, single-lane merchants, hospitality, car rental, and much more.
- **Consumer Intuitive:** Equipped with LEDs and sound to provide visual and audible cues to enable smooth and seamless transactions.
- **Flexible install:** Direct serial connection, Dynamic Strip™ and ViVOSmartcable™ technologies allow for flexibility when connecting to ECR and POS systems.
- **Secure:** Secure Transactions with ISO/IEC 14443 Type A/B chip cards in conjunction with dynamic CVV/CVC.
- **Intellectual Property:** Protected by several patent-pending applications.

SPECIFICATIONS

Hardware

Contactless 13.56 MHz
Interface: ISO 14443 Type A/B, Mifare®, NFC

Physical

Height: (Unfolded) 5 inches (125.0 mm)
(Folded) 2.5 inches (62.5 mm)
Width: (Widest) 4.2 inches (105 mm)
Depth: .7 inches (10 mm)

Environmental

Operating Temp.: 0 to 40 c (32 to 104 F)
Storage Temp.: -18 to 70 c (0 to 158 F)
Operating Humidity: 20% to 90% non-condensing

Power

Voltage: 120 VAC, 60 Hz (US)
220 VAC, 50 Hz (International)